

PRODUCT: 57 PSA REV082818

PRODUCT DESCRIPTION: 2 mils low surface energy acrylic pressure sensitive adhesive

PSA

Physical Property	Description - Value	Test Standard
Material	Acrylic	
Type	PET Coated LSE	
Thickness	2 mils	
Peel Adhesion	100 oz/in	PSTC-101 Modified
Loop Tack	160 oz/ sq. in	PSTC-16
Holding Power (1000g on 1 sq. in)	24+ hours	PSTC-107
Temperature Resistance	-30 °F to 250 °F	
Liner type and thickness	PET, 2mil	

AVAILABLE SIZES

Roll	54" X 250 LY
Sheet	As Specified

Compliance Features:

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.