

**PRODUCT: 91 PSA**

**REV052323NT**

**PRODUCT DESCRIPTION:** Double-coated rubber pressure sensitive adhesive.

Physical Property	Description - Value
Material	Rubber
Type	Double-Coated Tape
Liner Type	5.5 mil (0.14 mm) Kraft paper
Carrier Type	0.5 mil (0.013 mm) PET Film
Thickness	3 mil (0.08 mm)
Service Temperature	30 to 150 °F (-1 to 66 °C)
Shear Strength (PSTC 107 Mod)	>24 Hours

Peel Adhesion to Steel:

Substrate Material	Results		Test Method
	Air Side	Liner Side	
1 mil PET	9.056 lb/in (1.586 N/mm)	7.811 lb/in (1.368 N/mm)	PSTC 101 Mod
2 mil Al Foil	14.37 lb/in (2.516 N/mm)	13.74 lb/in (2.407 N/mm)	PSTC 101 Mod

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement, or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.