

**PRODUCT: 92 PSA REV082415**

**PRODUCT DESCRIPTION: 2 mils acrylic pressure sensitive adhesive**

**PSA**

Physical Property	Description - Value	Test Standard
Material	Acrylic	
Type	Unsupported	
Thickness	2 mils	
Peel Adhesion, 1 mil Polyester	50 oz/in	PSTC #101, 24 Hr Dwell
Peel Adhesion, 2 mil dead soft aluminum foil	150 oz/in	PSTC #101, 24 Hr Dwell
Shear Adhesion, one minute Max Dwell	7 days	PSTC #107 @72 °F, 1000gm/sq. in
Shear Adhesion, one minute Max Dwell	7 days	PSTC #107 @150 °F, 500gm/sq. in
Temperature range	-30 °F to 220 °F	Intermittent to 250°F
Liner type and thickness	74 lb, 5.5 mils	

**AVAILABLE SIZES**

Roll	54" X 500 LY
Sheet	As Specified

**Compliance Features:**

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.