

**PRODUCT: 97 PSA REV082415**

**PRODUCT DESCRIPTION: 3 mils acrylic pressure sensitive adhesive**

**PSA**

Physical Property	Description - Value	Tolerance	Test Standard
Material	Acrylic		
Type	Unsupported		
Thickness	3 mils	+/- 0.3 mil	
Thickness – PET Release Liner	2 mils		
Peel Adhesion – Exposed Side	50 oz/inch width		PSTC #101 Method E, backed with 1 mil polyester, 24 hr dwell
Peel Adhesion – Exposed Side	150 oz/inch width		PSTC #101 Method E, backed with 2 mil Aluminum, 24 hr dwell
Liner	2-mil Silicone coated polyester liner		
Shear Adhesion – Exposed Side	168 Hours		PSTC#107, Modified; 1000gm/sq.in at 72°F, 1 min dwell
Shear Adhesion	18 Hours		PSTC#107, Procedure A, modified; 1000gm/sq. in at 150°F, 1 min dwell
Temperature Range	-30° to 220°F		

**AVAILABLE SIZES**

Roll	54" X 300 LY
Sheet	As Specified

**Compliance Features:**

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.