

**PRODUCT:**

**99 PSA**

**REV082415**

**PRODUCT DESCRIPTION:**

Unsupported acrylic permanent pressure-sensitive adhesive

**PSA**

Physical Property	Description - Value	Test Standard
Material	Acrylic	
Type	Unsupported	
Thickness – Adhesive Exposed Side	3.0 mils	
Thickness - liner	5.5 mils	
Peel Adhesion – Liner Side	58 oz/inch	PSTC #101 Method E; backed with 1 mil polyester, 24 hr dwell
Peel Adhesion – Liner Side	160 oz/inch	PSTC #101 Method E; backed with 2 mil dead soft aluminum foil, 24 hr dwell
Shear Adhesion – Liner Side	7 days minimum	PSTC#107, Procedure A, modified, 1000gm/sq.in at 72°F
Shear Adhesion – Liner Side	7 days minimum	PSTC#107, Procedure A, modified, 500gm/sq.in at 150°F
Temperature Range	-30°F to 250°F	

**Features**

- High tack 3 mil acrylic adhesive
- Available in 54" & 64" useable widths
- Bonds well to a variety of substrates
- Excellent peel and shear properties

**Compliance Features:**

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.