

PRODUCT:

AP

REV082015

PRODUCT DESCRIPTION:

Aluminized Polyester Film

Physical Property	Description - Value	Test Standard
Material	Aluminized polyester film	
Thickness	1.7 mil +/- 10%	
Color	Metalized	
Weight	28.4 lbs/ream	
Surface Density	0.15 oz/sq. ft	
Application Temperature	220°F – 280°F	
Tensile Strength at Break – Machine Direction	19 kg/sq. mm	ASTM-D-882
Tensile Strength at Break – Transverse Direction	20 kg/sq. mm	ASTM-D-882

Compliance Features:

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.