

**PRODUCT: PC REV082115**

**PRODUCT DESCRIPTION:** Black PVC coated perforated fabric facing.

**FACING**

Physical Property	Description - Value	Test Standard
Material	PVC coated fabric	
Open Area	14%	
Thickness	0.55 mm ( $\pm 10\%$ )	ASTM-D-751
Width	57 inches (+1 inch)	ASTM-D-751
Weight	23 oz/linear yard ( $\pm 2$ oz/linear yard)	ASTM-D-751
Coating Adhesion	3.0 lb minimum Machine & Cross Direction	ASTM-D-751
Tensile Strength	35 lb minimum Machine & Cross Direction	ASTM D 751
Tearing Strength	5.5 lb minimum Machine & Cross Direction	ASTM D 5587
Cold Crack	-20 °F	FED 191A-5874
UV Stabilized Pigments (QUV:300 Hrs)	3.5 minimum at 500 hours gray scale	ASTM G53
Flammability Standards	Pass	FMVSS-302
Surface Abrasion- Wyzenbeek	No Change at 50,000 cycles	ASTM D4157-02

**Compliance Features:**

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.