

PRODUCT:

-PG-

REV031423NT

PRODUCT DESCRIPTION: Perforated Gray 18% Open Area.

Physical Property	Description - Value		Test Method
Material	Substrate – Polyester Headliner Pattern		
Gauge/Thickness	22 mil (0.55 mm) +/- 10%		
Width	57 in -0, +1 in (1.4 m -0, +0.0254 m)		
Basis Weight	30 +/- 2.5 oz/lin yd (0.93 +/- 0.078 kg/lin m)		ASTM D 751
	Machine Direction	Cross Direction	
Tensile Strength (minimum)	112 lb (500 N)	67.4 lb (300 N)	CFFA-17
Tearing Strength (minimum)	22.5 lb (100 N)	33.7 lb (150 N)	CFFA-16
Surface Abrasion (Wyzenbeek Abrasion)	Pass		Heavy Canvas
	Pass		SS Screen 50x70 mesh * 25,000 Cycles
Cold Crack @ -10 °F OR -23 °C	Pass		FED 191A-5874
Flammability	Pass		FMVSS 302
UV Stabilized Pigments	3.5 min		ASTM G 53 (QUV:500 hr)
Blocking Resistance	Pass		CFFA-4
Class Rating	Class A		ASTM D 3690

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.