

PRODUCT:

VPF-301-01-00-00

REV030315

PRODUCT DESCRIPTION: 1 lb/sf PVC barrier and 1/4 inch polyester urethane foam decoupler.

BARRIER

Physical Property	Description - Value	Tolerance
Material	Flexible PVC vinyl (polyvinylchloride)	
Color	Charcoal gray	
Weight	1.0 lb/sf	0.1 lb/sf
Flammability	MVSS-302	
Service Temperature	-40°F to 220°F	
Chemical Resistance	Excellent for most acids, mild alkalis, oils and grease	

FOAM

Physical Property	Description - Value	Tolerance	Test Standard
Material	Polyester Polyurethane Foam	NA	NA
Color	Charcoal	NA	NA
Density	2.0 lb/cf	+ - 0.2	ASTM D3574
Elongation	160%	minimum	ASTM D3574
Tensile Strength	18.0 psi	minimum	ASTM D3574
Tear Strength	1.90 pli	minimum	ASTM D3574
Flammability	MVSS302, UL-94 HF-1, SAE J369 SE/NBR		

AVAILABLE SIZES

Roll	54" X 25'
Sheet	54" X As Specified

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.