

PRODUCT:

VB

REV082415

PRODUCT DESCRIPTION:

PVC barrier

BARRIER

Physical Property	Description - Value
Material	Flexible PVC vinyl (polyvinylchloride)
Color	Charcoal gray
Specific Gravity	1.8 g/cc
Flammability	MVSS-302
Service Temperature	-40°F to 220°F
Chemical Resistance	Excellent for most acids, mild alkalis, oils and grease

ACOUSTICAL PROPERTIES

ASTM E90 and E413 on 1 lb/sf barrier only

Frequency (Hz)	125	250	500	1000	2000	4000	STC
TL (dB)	17	19	24	29	34	40	28

AVAILABLE SIZES

Roll	54" X 25'
Sheet	As Specified

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.