

**PRODUCT:**

**WR**

**REV082115**

**PRODUCT DESCRIPTION:** White Reinforced Polyester Film

**FACING**

Physical Property	Description - Value	Tolerance	Test Method
Material	White polyester film reinforced		
Thickness	0.005 inch	+/- 0.001 inch	ASTM-D-1777
Color	White		
Weight	1.8 oz/sy	+/- 5%	ASTM-D-3776
Tensile Strength - Warp	30 lbs/inch		ASTM-D-5035
Tensile Strength – Fill	25 lbs/inch		ASTM-D-5035
Tear Strength – Warp	21.16 oz		ASTM-D-1424
Tear Strength – Fill	14.11 oz		ASTM-D-1424
Beach Puncture	150 units (39.75 in/lbs)		ASTM-D-781
Temperature Resistance	-40°F to 300°F		
Permeability	0.05 Perms		ASTM-E-96
Corrosion Resistance	120°F at 95% RH 28 days		ASTM-C-1258

**Compliance Features:**

- Meets the Requirements of RoHS through June 2013 Revision of SVHC (Restriction of Hazardous Substances European Union Directive – 2002/95/EC)
- Compliant with European Union REACH (Registration, Evaluation and Authorization of Chemical Substances - EC1907/2006)

THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.